

09/21/00



35772 U.S. PTO

S&amp;H Form: PTO/SB/05 (9/99)

# UTILITY PATENT APPLICATION TRANSMITTAL

Attorney Docket No. 826.1622/JDH

First Named Inventor or Application Identifier:

Yasutaka ODA, et al.

Express Mail Label No.

(Only for new nonprovisional applications under 37 CFR 1.53(b))

09/21/00  
35772 U.S. PTO

## APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

ADDRESS TO: Assistant Commissioner for Patents  
Box Patent Application  
Washington, DC 20231

1. ☒ Fee Transmittal Form
2. ☒ Specification, Claims & Abstract ..... [ Total Pages: 84 ]
3. ☒ Drawing(s) (35 USC 113) ..... [ Total Sheets: 42 ]
4. ☒ Oath or Declaration ..... [ Total Pages: 4 ]
  - a. ☒ Newly executed (original or copy)
  - b. ☐ Copy from a prior application (37 CFR 1.63(d)) (for continuation/divisional with Box 17 completed)
    - i. ☐ **DELETION OF INVENTOR(S)**  
Signed statement attached deleting inventor(s) named in the prior application, see 37 CFR 1.63(d)(2) and 1.33(b).
5. ☐ Incorporation by Reference (usable if Box 4b is checked)  
The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied under Box 4b, is considered as being part of the disclosure of the accompanying application and is hereby incorporated by reference therein.
6. ☐ Microfiche Computer Program (Appendix)
7. ☐ Nucleotide and/or Amino Acid Sequence Submission (if applicable, all necessary)
  - a. ☐ Computer Readable Copy
  - b. ☐ Paper Copy (identical to computer copy)
  - c. ☐ Statement verifying identity of above copies

## ACCOMPANYING APPLICATION PARTS

8. ☒ Assignment Papers (cover sheet & document(s))
9. ☐ 37 CFR 3.73(b) Statement (when there is an assignee) [ ] Power of Attorney
10. ☐ English Translation Document (if applicable)
11. ☒ Information Disclosure Statement (IDS)/PTO-1449[X] Copies of IDS Citations (6)
12. ☐ Preliminary Amendment
13. ☒ Return Receipt Postcard (MPEP 503) (Should be specifically itemized)
14. ☐ Small Entity Statement(s) [ ] Statement filed in prior application, status still proper and desired.
15. ☒ Certified Copy of Priority Document(s) (if foreign priority is claimed) (Japanese Appln. 11-271916, filed 9/27/99)
16. ☐ Other:

## 17. If a CONTINUING APPLICATION, check appropriate box and supply the requisite information:

[ ] Continuation [ ] Divisional [ ] Continuation-in-part (CIP) of prior application No:         

## 18. CORRESPONDENCE ADDRESS



21171

PATENT TRADEMARK OFFICE

Staas &amp; Halsey

# NEW APPLICATION FEE TRANSMITTAL

Attorney Docket No. 826.1622/JDH  
 Application Number To be assigned  
 Filing Date September 21, 2000  
 First Named Inventor Yasutaka ODA, et al.

AMOUNT ENCLOSED \$1510.00



## FEE CALCULATION (fees effective 12/29/99)

CLAIMS	(1) FOR	(2) NUMBER FILED	(3) NUMBER EXTRA	(4) RATE	(5) CALCULATIONS
	TOTAL CLAIMS	18 - 20 =	0	X \$ 18.00 =	\$ 0.00
	INDEPENDENT CLAIMS	13 - 3 =	10	X \$ 78.00 =	780.00
	MULTIPLE DEPENDENT CLAIMS (any number; if applicable)			+ \$260.00 =	
	<b>BASIC FILING FEE</b>				690.00
	Total of above Calculations =				\$ 1470.00
	Surcharge for late filing fee, Statement or Power of Attorney (\$130.00)				+
	Reduction by 50% for filing by small entity (37 CFR 1.9, 1.27 & 1.28).				-
	<b>TOTAL FILING FEE =</b>				\$ 1470.00
	Surcharge for filing non-English language application (\$130.00; 37 CFR 1.52(d))				+
	Recordation of Assignment (\$40.00; 37 CFR 1.21(h)(1))				40.00
	<b>TOTAL FEES DUE =</b>				\$ 1510.00

## METHOD OF PAYMENT

- ☒ Check enclosed as payment.  
☐ Charge "TOTAL FEES DUE" to the Deposit Account No., below.  
☐ No payment is enclosed and no charges to the Deposit Account are authorized at this time.

## GENERAL AUTHORIZATION

- ☒ If the above-noted "AMOUNT ENCLOSED" is not correct, the Commissioner is hereby authorized to credit any overpayment or charge any additional fees necessary to:

Deposit Account No.

19-3935

Deposit Account Name

STAAS & HALSEY LLP

- ☒ The Commissioner is also authorized to credit any overpayments or charge any additional fees required under 37 CFR 1.16 (filing fees) or 37 CFR 1.17 (processing fees) during the prosecution of this application, including any related application(s) claiming benefit hereof pursuant to 35 USC § 120 (e.g., continuations/divisionals/CIPs under 37 CFR 1.53(b) and/or continuations/divisionals/CPAs under 37 CFR 1.53(d)) to maintain pendency hereof or of any such related application.

**SUBMITTED BY: STAAS & HALSEY LLP**

Typed Name	James D. Halsey, Jr.	Reg. No.	22,729
Signature		Date	September 21, 2000

APPLICATION FOR  
UNITED STATES LETTERS PATENT  
SPECIFICATION

INVENTOR(s): Yasutaka ODA, Katsumi HAYASHI,  
Masaya KIMURA, and Taichi UJIGAWA

Title of the Invention: DATA DELIVERING SYSTEM

## DATA DELIVERING SYSTEM

### Background of the Invention

### Field of the Invention

5           The present invention relates to a method for delivering data to devices connected via a communications network.

### Description of the Related Art

10           Generally, when data is delivered, a device at a delivery source must prepare the information identifying a delivery destination (hereinafter referred to as "destination information" or "delivery destination information"), and data to  
15 be delivered for each delivery destination.

          Fig. 1 explains an existing general data delivering system. This figure depicts the device at a data delivery source and an external storage medium accessed by this device. Note that this  
20 system is assumed to deliver data based on a user instruction (delivery request).

          A data managing unit 501 makes a data storing unit 502 collect the data corresponding to a user instruction. The data storing unit 502 obtains the  
25 data to be delivered to a user from an external storage

medium 511 according to an instruction from the data  
managing unit 501. Then, the data managing unit 501  
provides a data transferring unit 503 with the data  
collected by the data storing unit 502 and the  
5 destination information of that data. The data  
transferring unit 503 issues a data transfer  
instruction to a communication controlling unit 504.  
The communication controlling unit 504 then delivers  
the requested data to the user according to the data  
10 transfer instruction.

When data is delivered to a plurality of  
destinations with the above described system, the  
above stated process is repeatedly executed or a  
multi-cast transmission is performed if it is  
15 possible. The method repeating the above described  
process, however, imposes a heavy load on a device  
at a delivery source. On the other hand, the  
multi-cast transmission can only transmit the same  
data to all of destinations.

20 As a known method delivering data that differs  
depending on each destination, for example, Japanese  
Laid-open Patent Publication No. 6-152917 is known.  
This publication recites the technique with an  
improved merging capability. Hereinafter, the  
25 technique relating to Japanese Laid-open Patent

Publication No. 6-152917 is explained by referring to Figs. 2, 3A, and 3B.

Fig. 2 explains an existing data delivering system with a merging capability. This figure depicts a device at a data delivery source and an external storage media accessed by that device. Here, it is assumed that data in a common format (hereinafter referred to as "combined data") shown in Fig. 3A is generated and delivered to each destination. The combined data is composed of a variable portion which differs depending on each destination, and a common portion which is common to all of destinations.

A data managing unit 521 makes a common data storing unit 522 collect common data which is common element data to be delivered to a destination, for example, according to a user instruction. The common data storing unit 522 then collects the common data from an external storage medium 531, and passes the collected data to the data managing unit 521. This collected data is stored in the common portion of the combined data, but its variable portion is empty at this stage.

Next, the data managing unit 521 makes a variable data storing unit 523 collect variable data.

The variable data storing unit 523 therefore collects variable data from an external storage medium 532, and passes the collected data to the data managing unit 521. It should be noted that variable data  
5 includes destination information for identifying corresponding destination, and element data to be delivered to corresponding destination, for example, as shown in Fig. 3B.

The data managing unit 521 separates the  
10 variable data into the destination information and the element data. Then, the data managing unit 521 inserts (merges) element data-1 into the variable portion of the combined data, attaches destination information-1 to the combined data, and passes the  
15 combined data to a data transferring unit 524. The data transferring unit 524 issues a data transfer instruction to a communication controlling unit 525. The communication controlling unit 525 delivers the common data into which the element data-1 is inserted  
20 to the user identified by the destination information-1 according to the data transfer instruction. Thereafter, combined data into which element data-2 through element data-n are respectively inserted are delivered to respective  
25 users identified by destination information-2

through destination information-n.

In addition to the above described method, methods for delivering data that differs depending on each destination have been proposed. For example, the technique recited in Japanese Laid-open Patent Publication No. 63-16749, the technique recited in Japanese Laid-open Patent Publication No. 9-311831, etc. are proposed. With the former method, all candidate data to be inserted into a variable portion are delivered from a delivery source to destinations along with common data, and the users at the destinations respectively select necessary information. With the latter method, data is delivered in a form (image, audio, text, etc.) requested by each destination.

However, conventional data delivering methods have the following problems.

(1) A delivery source system must store all data to be delivered to corresponding destinations, or at least prepare all data to be delivered to corresponding destinations. Accordingly, the load on the delivery source system becomes heavy. Additionally, most of the known methods cannot start a data delivery until all data (to be delivered to all of destinations) are collected, when data that



differs depending on each destination is delivered. Therefore a data delivery delay becomes problematic in this case.

(2) A delivery source system must store the  
5 information about all of destinations (such as IP or mail addresses, system names, or the like). Therefore, the operations for managing destinations become complicated in the delivery source system.

(3) A delivery source system must generate (or  
10 assemble) all of delivery data, when data that differs depending on each destination is delivered. Therefore, the load on the delivery source system becomes heavy.

(4) All of delivery data are output from a delivery  
15 source system, when data that differs depending on each destination is delivered. Therefore, lines or paths adjacent to the delivery source system are occupied by that data delivery.

## 20 **Summary of the Invention**

An object of the present invention is to reduce a load on a delivery source in a data delivering system. Another object of the present invention is to improve data delivery efficiency.

25 A data delivering method according to the

present invention assumes a data delivery to a device connected via a network. With this method, structure information including the information for collecting element data is transmitted from a first  
5 to a second device, and the second device collects the element data according to the structure information and delivers the collected data to a third device.

With this method, the element data to be  
10 delivered to the third device is collected by the second device. That is, the first device does not need to collect the element data to be delivered to the third device. As a result, the load on the first device as a deliver source device is reduced.

15 With a data delivering method in another aspect of the present invention, structure information including first information for identifying the element data to be delivered to a destination device, second information for identifying a device that  
20 collects element data, and third information for identifying the destination device is generated, and the device identified by the second information collects the element data according to the first information, and delivers the collected element data  
25 to the destination device identified by the third

information.

With this method, a data delivery can easily be implemented in a wide variety of forms by the descriptions of the first to the third information.

5 For example, if a plurality of devices are specified in the second information, the plurality of specified devices can share a burden to collect the element data identified by the first information. As a result, a system with a high data delivery efficiency  
10 can be realized with ease.

In this method, a delivery destination group including a plurality of destination devices may be specified as the third information, and the device identified by the second information may  
15 deliver the element data to the plurality of destination devices belonging to the delivery destination group specified by the third information. In this method, a delivery source device does not need to recognize the addresses of final delivery  
20 destinations.

A data delivering method in a further aspect of the present invention assumes a data delivery from a delivery source device to a delivery destination device in a system including the delivery  
25 source device, a first relay device, and second and

third relay devices arranged in parallel. With this method, structure information is generated by the delivery source device, and first element data is collected by the first relay device according to the structure information. Furthermore, second element data is collected by the second relay device according to the structure information, and the first and the second element data are delivered from the second relay device to the delivery destination device that is connected to the second relay device. In the meantime, third element data is collected by the third relay device according to the structure information, and the first and the third element data are delivered from the third relay device to the delivery destination device that is connected to the third relay device.

With this method, when data that is partially common is delivered to a plurality of delivery destinations, the common data is collected by one device (a first relay device), and variable data that differs depending on each delivery destination is collected by a different device (the second and the third relay device). Accordingly, the common data is never be collected repeatedly, leading to a high data delivery efficiency.

**Brief Description of the Drawings**

Fig. 1 explains an existing general data delivering system;

5 Fig. 2 explains an existing data delivering system with a merging capability;

Fig. 3A exemplifies combined data;

Fig. 3B exemplifies variable data;

10 Fig. 4 shows a data delivering system according to one embodiment of the present invention;

Fig. 5 shows the configuration of a delivery source system;

Fig. 6 shows the configuration of a relay system

15 Fig. 7 shows the configuration of a resource system;

Fig. 8 shows the configuration of a delivery destination system;

Fig. 9 explains the format of structure information;

20 Fig. 10A exemplifies the structure information (No. 1);

Fig. 10B exemplifies a data delivery sequence (No. 1);

25 Fig. 11A exemplifies the structure information (No. 2);

Fig. 11B exemplifies the data delivery sequence (No. 2);

Fig. 12A exemplifies the structure information (No. 3);

5 Fig. 12B exemplifies the data delivery sequence (No. 3);

Fig. 13 exemplifies the structure information (No. 4);

10 Fig. 14 exemplifies the data delivery sequence (No. 4);

Fig. 15A exemplifies the structure information (No. 5);

Fig. 15B exemplifies the data delivery sequence (No. 5);

15 Fig. 16A exemplifies the structure information (No. 6);

Fig. 16B exemplifies the data delivery sequence (No. 6);

20 Fig. 17 is a flowchart explaining the operations of the delivery source system;

Fig. 18 is a flowchart showing the operations of the relay system;

Fig. 19 is a flowchart showing the operations of the resource system;

25 Fig. 20 is a flowchart showing the operations



information for each branch system (No. 2);

Fig. 32 exemplifies part of the structure  
information for each branch system (No. 3);

Figs. 33A and 33B exemplify assembly  
5 information;

Fig. 34 exemplifies assembled data generated  
by the headquarters system;

Fig. 35 exemplifies assembly information;

Fig. 36 exemplifies assembled data generated  
10 by an Asian branch system;

Fig. 37 exemplifies assembly information;

Fig. 38 exemplifies delivery data generated  
by a Japanese branch system;

Fig. 39 exemplifies assembly information used  
15 when data that differs depending on each subscriber  
is delivered;

Fig. 40 explains the method collecting element  
data for each subscriber;

Fig. 41 is a block diagram showing the  
20 configuration of a computer which executes programs  
describing the capabilities of the present  
invention; and

Fig. 42 explains the method providing software  
programs, etc., which relate to the present  
25 invention.



### **Description of the Preferred Embodiments**

Hereinafter, preferred embodiments according to the present invention will be explained by referring to the drawings.

Fig. 4 shows the configuration of a data delivering system according to one preferred embodiment of the present invention. With this system, data is delivered from a delivery source system 1 to one or a plurality of delivery destination systems 4. A method of the data delivery may be a push type (a method in which the delivery source system 1 spontaneously transmits data), or an on-demand type (a method in which the delivery source system 1 transmits data according to a request from the delivery destination system 4).

The delivery source system 1 is connected to the delivery destination systems 4 via relay systems 2a through 2c in this embodiment. That is, the relay systems 2a through 2c are connected subordinately to (or downstream from) the delivery source system 1, and the delivery destination systems 4 are connected subordinately to (or downstream from) the relay systems 2a through 2c. The relay systems 2a through 2c are connected in series and/or in parallel.

In the example shown in Fig. 4, the relay systems 2a and 2b are connected in series, and the relay systems 2a and 2c are connected in series. On the other hand, the relay systems 2b and 2c are connected  
5 in parallel. In other words, the relay systems 2b and 2c are connected on the same level of the subordinates (or the downstream) of the relay system 2a.

The present invention is not limited to this  
10 configuration. The number of connection stages of relay systems is not limited particularly. Additionally, the delivery source system 1 and the delivery destination systems 4 may directly be connected not via relay systems.

15 The relay systems 2a through 2c are connected to resource systems 3. The resource systems are positioned on the same levels as those of the corresponding relay systems 2a through 2c in this case. Furthermore, the resource systems 3 store the  
20 resources (data) to be delivered to the delivery destination systems 4. It should be remembered that the present invention is not limited to this configuration. For example, the delivery source system 1 or the delivery destination systems 4 may  
25 directly access the resource systems 3.

The delivery source system 1, the relay systems 2a through 2c, the resource systems 3, and the delivery destination systems 4 are connected via a network. The configuration of the network is not particularly limited. The network may be a wireless network, a network using optical fibers or metal cables, or a public or a private network. Also, communications protocols are not limited particularly.

10       The delivery source system 1 delivers data to the delivery destination systems 4 according to a request issued from the delivery destination systems 4 or spontaneously. If the delivery source system 1 itself holds or collects the data to be delivered  
15 to the delivery destination systems 4, it delivers the data to the delivery destination systems 4. Or, if the delivery source system 1 itself does not hold or collect the data to be delivered to the delivery destination systems 4, it generates a information  
20 set instructing to collect and to assemble data to be delivered to the delivery destination systems 4 (this information is hereinafter referred to as "structure information"), and transmits the generated information to the relay systems 2a through  
25 2c. Then, the relay systems 2a through 2c collect

the data to be delivered to the delivery destination systems 4 from the resource systems 3 according to the structure information, and deliver the collected data to the delivery destination systems 4. If the  
5 delivery source system 1 itself holds or collects part of the data to be delivered to the delivery destination systems 4, it delivers the data to the delivery destination systems 4, and also transmits the structure information for data that cannot be  
10 prepared to the relay systems 2a through 2c. Then, the relay systems 2a through 2c transfer the data transmitted from the delivery source system 1 to the delivery destination systems 4, and deliver the data that is collected from the resource systems  
15 3 according to the received structure information to the delivery destination systems 4.

Data delivered to the delivery destination systems 4 is composed of one or more pieces of element data. Accordingly, each element in the data to be  
20 delivered to the delivery destination systems 4 is hereinafter referred to as "element data" in some cases.

As described above, the delivery source system 1 can make other devices (the relay systems 2a through  
25 2c in this case) collect part or the whole of the

data to be delivered to the delivery destination systems 4. Accordingly, the storage device for storing the data to be delivered to the delivery destination systems 4 can be reduced in size in the delivery source system 1. Additionally, the load on the delivery source system 1 is reduced. Furthermore, since the element data (actual data) and the structure information (control information) are separated in this data delivering system, an efficient data delivery can be implemented.

Fig. 5 shows the configuration of a delivery source system. This delivery source system corresponds to the delivery source system 1 shown in Fig. 4.

A data managing unit 11 gives an instruction to generate structure information to a structure information generating unit 12 according to a user request or spontaneously, and manages generated structure information. The structure information, which will be described in detail later, includes relay system information, assembly information, element data information, and destination information. The managing unit 11 gives an instruction to collect element data from a storage medium 14 according to the structure information

to a data storing unit 13. Additionally, the data managing unit 11 gives an instruction to collect element data from a resource system (the resource systems 3 shown in Fig. 4) according to the structure information to a data transferring unit 16. The element data that is transferred from the resource system according to this instruction is received by a data receiving unit 15. The data managing unit 11 then manages the element data collected by the data storing unit 13 and the element data received by the data receiving unit 15. Furthermore, the data managing unit 11 gives to the data transferring unit 16 an instruction to transmit the structure information and the element data to a network.

The structure information generating unit 12 generates structure information according to the instruction from the data managing unit 11. The data storing unit 13 accesses the storage medium 14, and collects element data according to the instruction from the data managing unit 11. The storage medium 14 is a storage device that is arranged in this delivery source system, and stores element data.

The data receiving unit 15 receives element data from a resource system. The data receiving unit 15 is a device superordinate to a communication

controlling unit 17. The data transferring unit 16 issues an instruction to transfer element data to the resource system according to the instruction from the data managing unit 11. Furthermore, the data transferring unit 16 gives to the communication controlling unit 17 an instruction to transmit the structure information generated by the structure information generating unit 12, the element data collected by the data storing unit 13, and the element data received by the data receiving unit 15 to a network. The data transferring unit 16 is also a device superordinate to the communication controlling unit 17. The communication controlling unit 17 passes the data received from the network to the data receiving unit 15, and transmits the structure information and the element data to the network according to the instruction from the data transferring unit 16.

If the delivery source system does not or cannot collect the element data, it transmits only the structure information. Or, if the delivery source system has collected all of the element data defined by the structure information, it transmits the collected data to the network. The delivery source system may not deliver the structure information

to the relay system or the delivery destination system in this case. If the delivery source system has collected only part of the element data defined by the structure information, it transmits the collected element data to the network, and also transmits the structure information corresponding to the element data that cannot be collected to the network.

Fig. 6 shows the configuration of a relay system. This relay system corresponds to an arbitrary one of the relay systems 2a through 2c shown in Fig. 4. Note that the fundamental configuration and operations of the relay system are the same as those of a delivery source system.

A data receiving unit 21 receives structure information and/or element data, which are transmitted from a delivery source system (or another relay system). The data receiving unit 21 also receives element data from a resource system.

A data managing unit 22 gives to a data storing unit 23 an instruction to collect element data from a storage medium 24 according to the structure information received by the data receiving unit 21. If a destination group is set as delivery destination information in the structure information, the data



managing unit 22 gives to an inquiring unit 25 an instruction to inquire about a plurality of destinations corresponding to the destination group. The destination group represents, for example, a set of delivery destination systems or a set of relay systems. Furthermore, the data managing unit 22 gives to a data transferring unit 26 an instruction to collect element data from a resource system according to the structure information. The element data that is transferred from the resource system according to this instruction is received by the data receiving unit 21. The data managing unit 22 then manages the element data collected by the data storing unit 23 and the element data received by the data receiving unit 21. Furthermore, the data managing unit 22 gives to the data transferring unit 26 an instruction to transmit the structure information and the element data to the network.

The inquiring unit 25 accesses a destination database 27 according to the instruction from the data managing unit 22, and detects the plurality of destinations corresponding to the destination group set as the delivery destination information in the structure information. The correspondence between a destination group and the destinations

included in the destination group is registered to the destination database 27. This correspondence is assumed to be predetermined. The operations of the data storing unit 23, the storage medium 24, the data transferring unit 26, and the communication controlling unit 28 are fundamentally the same as those of the data storing unit 13, the storage medium 14, the data transferring unit 16, and the communication controlling unit 17 of the delivery source system shown in Fig. 5. Therefore, their explanations are omitted here.

As described above, the relay system collects element data according to the structure information transmitted from the delivery source system (or another relay system), and transmits the collected data to the delivery destination system (or the another relay system). If the relay system cannot collect all of the element data defined by the received structure information at this time, it transmits the structure information corresponding to the element data that cannot be collected to a network in addition to the element data.

Fig. 7 shows the configuration of a resource system. This resource system corresponds to an arbitrary one of the resource systems 3 shown in

Fig. 4. The fundamental configuration and operations of the relay system are the same as those of a delivery source system.

A data receiving unit 31 receives a data  
5 transfer request transmitted from a delivery source  
system, a relay system, or a delivery destination  
system. A data managing unit 32 gives to a data  
storing unit 33 an instruction to collect element  
10 data from a storage medium 34 according to the data  
transfer request received by the data receiving unit  
31. The data managing unit 32 manages the element  
data collected from the storage medium 34, and gives  
to a data transferring unit 35 an instruction to  
15 return the element data to the system which has issued  
the data transfer request. The data transferring  
unit 35 then gives to a communication controlling  
unit 36 an instruction to return the element data  
collected from the storage medium 34 to the system  
20 which has issued the data transfer request, according  
to the given instruction. The operations of the data  
storing unit 33, the storage medium 34, and the  
communication controlling unit 36 are fundamentally  
the same as those of the data storing unit 13, the  
storage medium 14, and the communication controlling  
25 unit 17 of the delivery source system shown in Fig.

5. Therefore, their explanations are omitted here.

Fig. 8 shows the configuration of a delivery destination system. This delivery destination system corresponds to an arbitrary one of the delivery destination systems 4 shown in Fig. 4. The fundamental configuration and operations of the delivery destination system are the same as those of a delivery source system.

A data receiving unit 41 receives the element data and/or the structure information, which are transmitted from a relay system (or a delivery source system). If the structure information is received by the data receiving unit 41, a data managing unit 42 gives to a data storing unit 43 an instruction to collect element data from a storage medium 44 according to the structure information. The data managing unit 4 also gives to a data transferring unit 45 an instruction to collect element data from a resource system. The element data that is transferred from the resource system according to this instruction is received by the data receiving unit 41.

If the structure information is received by the data receiving unit 41, the data managing unit 42 assembles element data received from the relay

system (or the delivery source system), the element data collected from the storage medium 44, and the element data collected from the resource system into result data, according to the assembly information

5 in the structure information. In this way, desired data can be obtained.

Fig. 9 explains the format of structure information. Structure information 50 is fundamentally generated in a delivery source system.

10 The structure information 50 includes relay system information 51, assembly information 52, element data information 53, and delivery destination information 54.

The relay system information 51 is the

15 information about a relay system that is to transmit structure information and element data. As the relay system information 51, for example, the information for identifying the location of a relay system on a network, such as the IP address or the

20 URL name of the relay system, etc. are used. Also a group name for identifying a relay system group composed of a plurality of relay systems, a category name for identifying a relay system group which is classified based on a particular concept, etc. may

25 be used as the relay system information 51.

The assembly information 52 is the information for assembling element data (and/or structure information). As the assembly information 52, for example, "attach", "merge", "compress", etc. are used. The element data information 53 is the information about element data which will be delivered to a delivery destination system. As the element data information 53, for example, the information for identifying the location of a system which stores element data on a network, such as a URL name, etc., and the information for identifying the type of the element data are used.

The delivery destination information 54 is the information about a destination to which element data (and structure information) are to be transmitted. As the delivery destination information 54, the information for identifying the location of a delivery destination system on a network, such as the IP address or the URL name of the delivery destination system, etc. are used. Also a group name for identifying a delivery destination system group composed of a plurality of delivery destination systems, a category name for identifying a delivery destination system group which is classified based on a particular concept,

and the like may be used as the delivery destination system information 54.

The data delivery sequence adopted in the data delivering system according to this preferred  
5 embodiment will be explained next.

The example shown in Figs. 10A and 10B is the case where a delivery source system, a relay system and a delivery destination system are provided with a ratio of 1:1:1. Here, a delivery source system  
10 61 delivers data to a delivery destination system 81 via a relay system 71.

Fig. 10A shows structure information generated by the delivery source system 61. In the relay system information in this structure information, the  
15 "relay system 71" is set. Furthermore, the "delivery destination system 81" is set in the delivery destination information.

The delivery source system 61 transmits the above described structure information to the relay  
20 system 71 as shown in Fig. 10B. Upon receipt of this structure information, the relay system 71 first collects corresponding element data from the storage medium provided with a resource system or the relay system 71 according to element data  
25 information-1 through element data information-n.

For example, if a URL name is used as the element data information, the relay system 71 obtains the element data from the site identified by the URL name. The relay system 71 then generates complete  
5 data to be delivered to the delivery destination system 81 by assembling the collected element data according to the assembly information in the structure information, and transmits the complete data to the delivery destination system 81. In this  
10 way, the delivery destination system 81 receives the complete data.

As described above, with this data delivering system, the relay system 71, which receives the structure information, collects the element data  
15 to be delivered to the delivery destination system 81, assembles the collected element data, and delivers the assembled data to the delivery destination system 81. Therefore, the delivery source system 61 does not need to collect the data  
20 to be delivered to a delivery destination system, so that the load on the delivery source system 61 is light. Furthermore, a storage device for storing the data to be delivered to the delivery destination system 81 can be reduced in size.

25 When data composed of a plurality of elements



is delivered, a plurality of pieces of element data information, and the assembly information for assembling the plurality of pieces of element data may be set in the structure information.

5 Accordingly, a wide variety of data can be delivered.

Figs. 11A and 11B exemplify the case where the same data is delivered to a plurality of delivery destination systems. That is, the case where a delivery source system, a relay system and delivery

10 destination systems are provided with a ratio of 1:1:m. Here, a delivery source system 61 delivers the same data to delivery destination systems 81-1 through 81-m via a relay system 71.

Fig. 11A shows the structure information

15 generated by the delivery source system 61. The "relay system 71" is set in the relay system information in the structure information. Furthermore, "delivery destination systems 81-1 through 81-m" are respectively set in delivery

20 destination information-1 through delivery destination information-m.

The delivery source system 61 transmits the structure information to the relay system 71 as shown in Fig. 11B. Upon receipt of the structure

25 information, the relay system 71 collects

corresponding element data according to the element data information-1 through element data information-n, and generates complete data according to assembly information, similar to the method explained by referring to Figs. 10A and 10B. The relay system 71 then transmits the complete data to the delivery destination systems 81-1 through 81-m according to the delivery destination information-1 through delivery destination information-m. In this way, the delivery destination systems 81-1 through 81-m receive the same complete data.

As described above, the same data can easily be delivered to a plurality of delivery destinations by setting a plurality of pieces of destination information in structure information in this data delivering system.

Figs. 12A and 12B exemplify the case where data is delivered via a plurality of relay systems. Here, a delivery source system 61 delivers data to a delivery destination system 81 via relay systems 71 and 72. In this case, the relay systems 71 and 72 are connected in series between the delivery source system 61 and the delivery destination system 81.

Fig. 12A shows the structure information generated by the delivery source system 61. This structure information is composed of structure information portions respectively for the relay systems 71 and 72. The "relay system 71" is set in the relay system information-1, whereas the "relay system 72" is set in the relay system information-2. Additionally, the "delivery destination system 81" is set in the delivery destination information.

10 The delivery source system 61 transmits the above described structure information to the relay system 71 as shown in Fig. 12B. Upon receipt of this structure information, the relay system 71 references the structure information portion for  
15 the relay system 71, collects element data according to element data information-1 through element data information-m, and assembles the collected element data according to assembly information-1. Furthermore, the relay system 71 transmits updated  
20 structure information to the relay system 72 after deleting the structure information portion for the relay system 71 from the received structure information. In this case, the destination is identified by the "relay system 2" in the structure  
25 information. Furthermore, the relay system 71

transmits to the relay system 72 also the element data (assembled data) assembled according to the assembly information-1.

Upon receipt of the structure information and  
5 the assembled data from the relay system 71, the relay system 72 executes the process complying with the structure information. Namely, the relay system 72 collects element data according to element data information-1 through element data  
10 information-n, and assembles the element data according to assembly information-2. Furthermore, the relay system 72 transmits to the delivery destination system 81 the assembled data received from the relay system 71 and the assembled data that  
15 the relay system 72 itself collects and assembles according to delivery destination information in the structure information. In this way, the delivery destination system 81 receives the data which are collected and assembled respectively by  
20 the relay systems 71 and 72.

Note that the element data information-1 through element data information-m set in the structure information portion for the relay system 71, and the element data information-1 through  
25 element data information-n set in the structure

information portion for the relay system 72 are fundamentally different from one another. However, some of them may be duplicate.

As described above, with this data delivering system, a plurality of relay systems, which connected in many stages, respectively collect and assemble element data according to structure information. Therefore, a delivery process is distributed, leading to an increase in a data delivery efficiency. Especially, loads on a relay system, a resource system, and a delivery destination system are optimized, so that the data delivery efficiency will further increase. As a method for distributing the loads, for example, a method equalizing the total amount of element data collected by each relay system, a method making a relay system, which is close to the storage location of element data to be collected, collect the element data, and the like are considered.

Figs. 13 and 14 exemplify the case where data including a common portion is delivered to a plurality of delivery destination devices. Here, a delivery source system 61 delivers data to a delivery destination system 81 via relay systems 71 and 72, and also delivers data to a delivery

destination system 82 via relay systems 71 and 73. Namely, the relay systems 71 through 73 form a tree structure.

Fig. 13 shows the structure information generated by the delivery source system 61. This structure information is composed of the structure information portions respectively for the relay systems 71, 72, and 73. The "relay systems 71 through 73" are respectively set in relay system information-1 through relay system information-3. Here, the relay system information-2 and relay system information-3 are assumed to be described as relay systems on the same level. Furthermore, the "delivery destination systems 81 and 82" are respectively set in the delivery destination information 1 and delivery destination information-2.

The delivery source system 61 transmits the above described structure information to the relay system 71 as shown in Fig. 14. Upon receipt of this structure information, the relay system 71 references the structure information portion for the relay system 71, collects element data according to element data information-1 through element data information-m, and assembles the collected element

data according to assembly information-1. Then, since the relay system information-2 and relay system information-3 are described as the relay systems on the same level, the relay system 71 transmits to the relay system 72 the structure information portion for the relay system 72 and also transmits to the relay system 73 the structure information portion for the relay system 73. In this case, the destinations are respectively identified by the relay system information-2 and relay system information-3 in the structure information. Additionally, the relay system 71 transmits the element data (assembled data) after being assembled according to the assembly information-1 to the relay systems 72 and 73.

Upon receipt of the structure information and the assembled data from the relay system 71, the relay system 72 collects element data according to element data information-1 through element data information-n, and assembles the collected element data according to assembly information-2 in a similar manner as in the case explained by referring to Fig. 12B. Furthermore, the relay system 72 transmits to the delivery destination system 81 the assembled data received from the relay system 71 and the

assembled data that the relay system 72 itself collects and assembles according to the delivery destination information-1 in the structure information. In this way, the delivery destination  
5 system 81 receives the data which are collected and assembled respectively by the relay systems 71 and 72.

The operations of the relay system 73 are fundamentally the same as those of the relay system  
10 72. Note that, however, the relay system 73 collects element data according to element data information-1 through element data information-k, and assembles the element data according to assembly information-3. Furthermore, the relay system 73 transmits to the  
15 delivery destination system 82 the assembled data received from the relay system 71 and the assembled data which is collected and assembled by the relay system 73. In this way, the delivery destination system 82 receives the data which are collected and  
20 assembled respectively by the relay systems 71 and 73.

As described above, this data delivering system provides with a plurality of relay systems, which are connected in a tree state, and common  
25 element data to be delivered to a plurality of



delivery destination systems is collected by one relay system, and a plurality sets of element data that differ depending on each delivery destination system are collected by different relay systems.

- 5 Accordingly, common element data which is delivered to a plurality of delivery destination systems is never be collected and delivered repeatedly, leading to an increase in a data delivery efficiency.

10 Figs. 15A and 15B exemplify the case where a delivery source system itself collects element data, and transmits the collected data to a delivery destination system. Here, a delivery source system 61 delivers data to a delivery destination system 81 not via a relay system.

- 15 Fig. 15A shows the structure information generated by the delivery source system 61. The "delivery source system 61" is set in relay system information in this structure information. Additionally, the "delivery destination system 81" is set in the delivery destination information.

20 Since the "delivery source system 61" is set in the relay system information in the structure information, the delivery source system 61 collects and assembles element data as shown in Fig. 15B.

25 That is, the delivery source system 61 collects

element data according to element data information-1 through element data information-n, and assembles the collected element data according to assembly information. Then, the delivery source system 61  
5 transmits the assembled element data (complete data) to the delivery destination system 81 according to the delivery destination information. In this way, the delivery destination system 81 receives the data which is delivered from the delivery source system  
10 61.

As described above, with this data delivering system, a delivery source system can collect and assemble element data by setting the delivery source system itself as relay system information in  
15 structure information with the same method as any of those implementing the data delivery, which are shown in Figs. 10 through 14. As a result, the merging capability explained as a conventional technique by referring to Figs. 2, 3A, and 3B can  
20 easily be implemented.

Figs. 16A and 16B exemplify the case where only an instruction to collect and assemble element data is delivered from a delivery source system to a delivery destination system, and the delivery  
25 destination system collects and assembles element

data according to this instruction. Here, the instruction (structure information) is delivered from a delivery source system 61 to a delivery destination system 81, and the delivery destination  
5 system 81 collects and assembles element data according to this instruction.

Fig. 16A shows the structure information generated by the delivery source system 61. In both relay system information and delivery destination  
10 information in this structure information, the "delivery destination system 81" is set.

The delivery source system 61 transmits the above described structure information to the delivery destination system 81 as shown in Fig. 16B.  
15 Since the "delivery destination system 81" is set as the relay system information, the delivery destination system 81 collects and assembles element data upon receipt of this structure information. Namely, the delivery destination system 81 collects  
20 element data according to element data information-1 through element data information-n, and assembles the collected element data according to assembly information. In this way, the delivery destination system 81 obtains desired data.

25 With this data delivering system, a delivery

source system only transmits an instruction to collect and assemble element data to a delivery destination system as described above, so that the load on the delivery source system is light.

5       Next, the operations of a delivery source system, a relay system, a resource system, and a delivery destination system are respectively explained by referring to flowcharts. In the following explanations, data which is assembled from  
10   a part of desired element data and is to be delivered to a delivery destination system is referred to as "assembled data", and final data which is assembled from all desired element data and is to be delivered to a delivery destination system is referred to as  
15   "complete data".

Fig. 17 is a flowchart explaining the operations of a delivery source system. This process is executed upon receipt of a data delivery request issued from a user, or at the start of a  
20   spontaneous data delivery. A delivery source system spontaneously starts a data delivery, for example, in the case where newspaper data is delivered to a subscriber who makes a contract to receive a newspaper as electronic data at a  
25   predetermined time every day.

In step S1, (1) information for identifying a storage location of element data to be delivered to a delivery destination system (element data information), (2) information for assembling the element information (assembly information), and (3) information for identifying a system which collects the element data (relay system information) are generated based on a data delivery request from a user or preregistered information. In step S2, structure information is generated by attaching the delivery destination information for identifying a delivery destination system to the information generated in step S1.

In step S3, it is examined whether or not a delivery source system itself is set as the relay information in the structure information. If the delivery source system is set as the relay system information, the process goes to step S4. Otherwise, the process skips steps S4 through S9.

In step S4, the element data information in the structure information is analyzed. In step S5, it is examined whether or not the delivery source system is set as the element data information. If the delivery source system is set as the element data information, corresponding element data is

obtained from a storage medium (the storage medium 14 shown in Fig. 5) comprised by the delivery source system in step S6. At this time, the data storing unit 13 shown in Fig. 5 is started up. If the delivery source system is not set as the element data information, corresponding element data is obtained from the resource system identified by the element data information in step S7. If both of the delivery source system itself and a resource system are set as the element data information, the operations in both of steps S6 and S7 are performed.

In step S8, the element data obtained in step S6 and/or step S7 is assembled according to assembly information. In this way, assembled data or complete data is generated. In step S9, the structure information is updated. Specifically, the data portion for the delivery source system is deleted from the structure information generated in step S2.

In step S10, it is examined whether or not delivery destination information is attached to the structure information portion for the delivery source system. If the delivery destination information is attached to the structure information portion for the delivery source system, the assembled

data or complete data generated in step S8 is delivered to the delivery destination system according to the delivery destination information in step S11. If the delivery destination information is not attached to the structure information portion for the delivery source system, the structure information or the structure information plus assembled data is delivered to a corresponding relay system according to the relay system information. If step S6 and/or step S7 is executed, the structure information plus assembled data is transmitted. If these steps are not executed, only the structure information is transmitted.

As described above, the delivery source system generates structure information, and transmits the structure information or the structure information plus assembled data according to the structure information. If the delivery source system itself is set as the relay system information as in the example shown in Fig. 15A, steps S4 through S9 of this flowchart are executed.

Fig. 18 is a flowchart explaining the operations of a relay system. The process of this flowchart is executed when structure information or structure information plus assembled data is

received from a delivery source system or a superordinate relay system.

In step S21, structure information or structure information plus assembled data is received. For example, the relay system 2a shown in Fig. 4 receives these data from the delivery source system 1. In the meantime, for example, the relay system 2b or 2c shown in Fig. 4 receives these data from the relay system 2a.

The operations in step S22 through S30 are fundamentally the same as those in steps S4 through S12, which are shown as the operations of the delivery source system in Fig. 17. Note that, however, element data is obtained from the storage medium (the storage medium 24 shown in Fig. 6) comprised by the relay system in step S24. In step S30, the structure information or the structure information plus assembled data is transmitted to a subordinate (downstream) relay system.

For instance, if a plurality of pieces of delivery destination information are set in the structure information as in the example shown in Fig. 11A, the same delivery data is transmitted to the delivery destination systems identified by the plurality of pieces of delivery destination



information in step S29. Furthermore, for instance, if a plurality of pieces of relay system information are described as relay systems on the same level as in the example shown in Figs. 13 and 14, the same data (structure information or structure information plus assembled data) is delivered to the respective relay systems identified by the plurality of pieces of relay system information in step S30.

10 As described above, the relay system collects and assembles element data according to structure information upon receipt of the structure information, and delivers the element data to a delivery destination system or its subordinate relay system.

15 Fig. 19 is a flowchart showing the operations of a resource system. The process of this flowchart is executed upon receipt of an element data transfer request issued from a delivery source system, a relay system, or a delivery destination system.

In step S41, the element data transfer request is received from the delivery source system, the relay system, or the delivery destination system. In step S42, corresponding element data is obtained from the storage medium (the storage medium 34 shown

in Fig. 7) comprised by the resource system according to the received data transfer request. At this time, the data storing unit 33 shown in Fig. 7 is started up. Then, in step S43, the obtained  
5 element data is returned to the system which has issued the data transfer request. As described above, the resource system provides corresponding element data according to a data transfer request.

Fig. 20 is a flowchart showing the operations  
10 of a delivery destination system. The process of this flowchart is executed upon receipt of structure information, structure information plus assembled data, or complete data from a delivery source system or a relay system.

15 In step S51, the structure information, the structure information plus assembled data, or the complete data is received. By way of example, the delivery destination system 81 shown in Fig. 10 receives delivery data from the relay system 71.  
20 Additionally, for instance, the delivery destination system 81 shown in Fig. 15 receives complete data from the delivery source system 61. Furthermore, by way of example, the delivery destination system 81 shown in Fig. 16 receives  
25 structure information from the delivery source

system 61.

In step S52, it is examined whether or not the received data is complete data. This examination is made by determining whether or not structure information is received. That is to say, if the structure information is not received, it is regarded that complete data is received and the process is terminated. If the structure information is received, the operations in and after step S53 are executed.

The operations in steps S53 through S57 are fundamentally the same as those in steps S4 through S8, which are shown as the operations of the delivery source system shown in Fig. 17. Note that, however, element data is obtained from the storage medium (the storage medium 44 shown in Fig. 8) comprised by the delivery destination system in step S55.

As described above, the delivery destination system receives complete data from the delivery source system or the relay system, or obtains complete data according to received structure information.

Next, more specific embodiments of the data delivering method according to the present invention will be described.

#### First Embodiment

The first embodiment relates to a newspaper delivering system which delivers newspaper articles to subscribers as electronic data. The data delivering method shown in Figs. 13 through 15 is used in this system.

With this newspaper delivering system, each subscriber can receive nationwide and local news. To implement such a data delivery, a headquarters system 101 provides all of subscribers with the nationwide news to be delivered, and branch systems 103a through 103c (a branch-A system 103a through a branch-C system 103c) respectively provide the subscribers with local news. Here, the headquarters system 101 functions as a delivery source system, whereas the branch systems 103a through 103c function as relay systems respectively.

Fig. 22 exemplifies the structure information used in the first embodiment. This structure information includes the structure information portion for the headquarter system 101, and the structure information portions for the respective branch systems 103a through 103c.

In the structure information portion for the

headquarters system 101, the "headquarters system",  
"attach", and "nationwide news" are respectively  
set as relay system information, assembly  
information, and element data information.

5 Accordingly, the headquarters system 101 itself  
obtains the nationwide news, and delivers the  
obtained news to the branch systems 103a through  
103c. Here, the nationwide news is assumed to be  
stored in a resource system 102. Furthermore, since

10 the relay system information in the structure  
information portions for the respective branch  
systems 103a through 103c are described as relay  
systems on the same level, the headquarters system  
101 transmits the respective structure information

15 portions to the branch systems 103a through 103c.

The branch system 103a (branch-A system)  
receives the nationwide news, and the structure  
information portion for the branch system 103a.  
"Assembled data plus local news" and "local news"

20 are respectively set as assembly information and  
element data information in the structure  
information portion for the branch system 103a.  
Here, the "assembled data" is the "nationwide news".  
Accordingly, the branch system 103a obtains the

25 "local news" from the resource system 104, and

assembles complete data from the "nationwide news" received from the headquarters system 101 and the "local news". The branch system 103a then delivers the nationwide news and the local news to the  
5    respective subscribers (delivery destinations A-1 through A-n) according to the delivery destination information in the structure information portion.

In this way, the subscribers (delivery destinations A-1 through A-n) who make contracts  
10    with the branch-A can receive the "nationwide news" prepared by the headquarters and the "local news" prepared by the branch-A. Remember that similar deliveries are made by the branch-B and branch-C.

As described above, with the newspaper  
15    delivering system according to the first embodiment, data that differs depending on each delivery destination can be attached to common data when the common data is delivered to a plurality of delivery destinations.

20    The above described embodiment assumes that the headquarters system 101 recognizes all of delivery destinations. However, the headquarters system 101 does not always need to recognize all of delivery destinations. For example, if  
25    subscriber information is managed by the branch

systems 103a through 103c, the headquarters system 101 sets the information for identifying a group to which a plurality of delivery destinations belong, as the delivery destination information in the structure information, which is to be notified to the branch systems 103a through 103c, as shown in Fig. 23.

The branch systems 103a through 103c respectively possess a delivery destination list for managing delivery destinations. The delivery destination list possessed by the branch system 103a is exemplified in Fig. 24. By way of example, upon receiving from the headquarters system 101 the structure information in which "subscribers" are set as delivery destination information, the branch system 103a references the delivery destination list and delivers corresponding data to the delivery destinations A-1 through A-n.

Fig. 25 is a flowchart explaining the operations of a relay system upon receipt of structure information in which a group is set as delivery destination information. It should be remembered that the process for collecting and assembling element data is omitted from this flowchart.

In step S61, delivery destination information in the received structure information is analyzed. In step S62, it is examined whether or not the delivery destination information is registered as a group name included in a delivery destination list. If the information is registered as a group name, all of delivery destinations corresponding to the group name are extracted from the delivery destination list in step S63. In step S64, corresponding data is transmitted to the respective delivery destinations extracted from the delivery destination list. If the delivery destination information in the received structure information is not registered to the delivery destination list, corresponding data is transmitted to delivery destinations according to the delivery destination information in step S65. The operations in steps S61 through S63 are executed by the inquiring unit 25 shown in Fig. 6. Furthermore, the delivery destination list is stored in a destination database 27.

A method specifying a plurality of delivery destinations by using a delivery destination group may be utilized in various forms in addition to a newspaper delivering system. This method is also



useful, for example, when an in-house newsletter is transmitted from headquarters to branches, sales offices, plants, etc. In this case, the headquarters does not need to set each employee address in structure information, and may only set the information representing "employees" as delivery destination information. This is similar also when each branch forwards a received in-house newsletter to its subordinate sales offices. Then, each branch, each sales office, and each plant deliver the in-house newsletter to employees who belong thereto.

The above described example refers to the case where delivery destinations are put into groups. However, relay systems may be put into groups alternatively. For example, the relay systems 72 and 73 may be put into a group in the example shown in Fig. 14. In this case, the delivery source system 61 regards the relay systems 72 and 73 as one group, and sets the information for identifying the group in structure information. Additionally, the relay system 71 possesses a relay system list for managing the grouping of relay systems, and delivers corresponding data to a plurality of relay systems by using this list.

## Second Embodiment

The second embodiment relates to an operational data delivering system which delivers  
5 the information about operations from a general affairs division in a company to respective employees. This system utilizes the data delivering method shown in Figs. 15 and 16.

The operational data delivering system  
10 according to this embodiment assumes that templates (such as a spreadsheet format) of a job achievement (business performance) report, an in-office memo, a business trip expense adjustment statement are distributed to employees beforehand.  
15 These templates may be distributed by using a storage medium such as a CD-ROM, a floppy disk, etc., or via a network. In either case, these templates are assumed to be prestored onto a storage medium 114 (hard disk, etc.) comprised by a terminal 113 for  
20 each employee. A general affairs division system 111 periodically delivers the raw data of the job achievement report, the in-office memo, and the business trip expense adjustment statement to each employee, and the employees display the received  
25 data by using the templates which are distributed

beforehand.

To implement this data delivery, the general affairs division system 111 generates the structure information shown in Fig. 26B, and performs a data  
5 delivery according to the structure information. In this example, since the "general affairs division system" is set as the relay system information in the structure information, the general affairs division system 111 collects job achievement data,  
10 in-office memo data, and business trip expenses adjustment data from the resource system 112, and delivers the collected data to the terminal 113. At this time, the general affairs division system 111 notifies the terminal 113 of the structure  
15 information for the terminal 113.

Upon receipt of this structure information, the terminal 113 extracts a corresponding template from the storage medium 114 according to the element data information, and embeds the job achievement  
20 data, the in-office memo data, or the business trip expense adjustment data into the template according to assembly information. In this way, an employee-A can view the job achievement report, the in-office memo, or the business trip expense adjustment  
25 statement in the predetermined format.

As described above, with the system according to this embodiment, not fixed data but only variable data is delivered, which leads to a high data transfer efficiency.

5

### Third Embodiment

The third embodiment relates to a newspaper delivering system which delivers newspaper articles to subscribers as electronic data. In this system, the structure data is described in an XML (eXtensible Markup Language).

With this newspaper delivering system, world news is delivered from headquarters to branches, and is further delivered to subscribers after local news (Asian news, Japanese news, or the like) is attached by each of the branches depending on need.

Specifically, a headquarters system 201 is arranged in New York, and comprises a database 202 for storing "world news". Additionally, the headquarters system 201 comprises a subscriber list 203 for storing subscriber information (including addresses). This subscriber list 203 stores the information of United States and Yugoslavian subscribers. The headquarters system 201 delivers "world news" to US subscribers U-1 through U-n, and

also delivers the news to a Yugoslavian branch system 211 and an Asian branch system 221.

The Yugoslavian branch system 211 delivers the "world news" received from the headquarters system 201 to the Yugoslavian subscribers Y-1 through Y-n. Addresses of delivery destinations, etc. are provided from the headquarters system 201.

The Asian branch system 221 comprises a database 222 for storing "Asian news", and a subscriber list 223 for storing the information of subscribers in Asian areas except for Japan. The Asian branch system 221 attaches the "Asian news" to the "world news" received from the headquarters system 201, delivers the set of news to subscribers A-1 through A-n in the Asian areas, and also delivers the them to a Japanese branch system 231.

The Japanese branch system 231 comprises a database 232 for storing "Japanese news", and a subscriber list for storing the information of subscribers inside Japan. The Japanese branch system 231 attaches "Japanese news" to the "world news" and "Asian news" received from the Asian branch system 221, and delivers the set of news to the subscribers J-1 through J-n inside Japan.

To implement the above described data delivery,

the headquarters system 201 generates the structure information shown in Fig. 28. This structure information (1) includes the structure information portion (2) for the headquarters system 201, the  
5 structure information portion (3) for the Yugoslavian branch system 211, and the structure information portion (4) for the Asian areas (including Japan). The structure information portion (4) includes the structure information  
10 portion (5) for the Asian branch system 221, and the structure information portion (6) for the Japanese branch system 231. The structure information portions (2), (3), (5), and (6) are respectively shown in Figs. 29 through 32. In the  
15 structure information, relay system information, assembly information, element data information, and delivery destination information are respectively described by using <gateway>, <structure>, <data list>, and <receptionist list>.

20       A relay system "newyork@delivery.com" specified by a gateway tag is assumed to represent the headquarters system 201 in Fig. 28 or 29.

      The headquarters system 201 first analyzes the element data information in the structure  
25 information portion (2). Namely, a data\_list tag

is analyzed. Here, a database 202 of the headquarters system 201 is described as a storage location of the element data to be collected by the headquarters system 201 in the data\_list tag.

5 Accordingly, the headquarters system 201 starts up a data storing unit within the headquarters system 201, and obtains element data "world\_news.xml" from the database 202.

The headquarters system 201 then generates  
10 assembled data by assembling the element data according to the assembly information in the structure information portion (2). Namely, the assembled data is generated according to the description of a structure tag. The assembly  
15 information is exemplified in Figs. 33A and 33B. These two assembly information are substantially the same. That is, "world\_news.xml" is specified as data to be delivered, and date and year, a version number, etc. are further described. The assembly  
20 information shown in Fig. 33B is different from that shown in Fig. 33A in the point that element data information (a data list) is described.

Fig. 34 exemplifies the assembled data generated by the headquarters system 201 according  
25 to the assembly information in the structure

information portion (2). "world\_news.xml" is embedded into a world\_news tag in this assembled data. The process generating the assembled data according to assembly information is executed by  
5 a data managing unit.

The headquarters system 201 delivers the assembled data to delivery destinations according to the delivery destination information in the structure information portion (2). Namely, the  
10 assembled data is delivered to subscribers U-1 through U-n according to the description of the receptionist-list tag. In this way, the subscribers U-1 through U-n receive "world\_news.xml". Then, the headquarters system  
15 201 deletes the structure information portion (2) from the structure information (1).

Furthermore, the headquarters system 201 analyzes the delivery\_info tag shown in Fig. 28 in order to deliver the remaining structure information  
20 to relay systems. Here, the delivery\_info tags in the structure information portions (3) and (4) are described on the same level. Accordingly, the headquarters system 201 separates the remaining structure information into the structure  
25 information portions (3) and (4), and delivers the



separated portions according to the respective relay system information. Namely, the structure information portion (3) is delivered to the Yugoslavian branch system (yugo@delivery.com) 211 according to the description of its gateway tag, whereas the structure information portion (4) is delivered to the Asian branch system (asia@delivery.com) 221 according to the description of its gateway tag. At this time, the headquarters system 201 delivers the assembled data "news.xml" to the Yugoslavian branch system 211 and the Asian branch system 221. This assembled data "news.xml" includes "world\_news.xml".

In this way, the Yugoslavian branch system 211 receives "world\_news.xml" and the structure information portion (3), whereas the Asian branch system 221 receives "world\_news.xml" and the structure information portion (4).

The Yugoslavian branch system 211 analyzes the element data information in the structure information portion (3) shown in Fig. 28 or 30. That is, the data\_list tag is analyzed. Since no protocol name specification is included in this data\_list tag, the Yugoslavian branch system 211 recognizes that there is no element data to be collected except

for the assembled data received from the headquarters system 201. Additionally, because no assembly information is described in the structure information portion (3), no process is performed

5 for the assembled data received from the headquarters system 201. The Yugoslavian branch system 211 then delivers the assembled data received from the headquarters system 201 to respective delivery destinations according to the delivery destination

10 information in the structure information portion (3). Namely, the assembled data is delivered to the subscribers Y-1 through Y-n according to the description of the receptionist\_list tag. In this way, the subscribers Y-1 through Y-n receive

15 "world\_news.xml".

Then, the Yugoslavian branch system 211 deletes the structure information portion (3) from the received structure information. In this case, no data is left as the structure information.

20 Accordingly, the entire process is regarded as being completed, and the data delivery process is terminated in the Yugoslavian branch system 211.

In the meantime, the Asian branch system 221 analyzes the element data information in the

25 structure information portion (5) shown in Fig. 28

or 31. Namely, the data\_list tag is analyzed. As  
a result, the assembled data "news.xml" received  
from the headquarters system 201, and the element  
data "asian\_news.xml" stored in a database 222 are  
5 recognized. Accordingly, the Asian branch system  
221 extracts element data "asian\_news.xml" from the  
database 222 according to the element data  
information.

Next, the Asian branch system 21 generates  
10 assembled data by assembling the element data  
according to the assembly information in the  
structure information portion (5). That is, the  
assembled data is generated according to the  
description of the structure tag. The assembly  
15 information is exemplified in Fig. 35. In this  
assembly information, the assembled data "news.xml"  
received from the headquarters system 201, and  
"Asian\_news.xml" extracted from the database 222  
are specified as data to be delivered.

20 Fig. 36 exemplifies the assembled data  
generated by the Asian branch system 221 according  
to the assembly information in the structure  
information portion (5). In this assembled data,  
"asian\_news.xml" is embedded into the asian\_news  
25 tag in this assembled data, and "world\_news.xml"

is embedded into the world\_news tag.

The Asian branch system 221 delivers the assembled data to delivery destinations according to the delivery destination information in the structure information portion (5). Namely, the data delivery is executed according to the description of the receptionist\_list tag. However, the addresses of the delivery destinations are not described, but only a category "asia" is specified in the receptionist\_list tag. Accordingly, the Asian branch system 221 accesses a subscriber list 223 by using this category name as a key and recognizes the delivery destinations belonging to the category "asia". Then, the Asian branch system 221 delivers the assembled data including "asian\_news.xml" and "world\_news.xml" to the subscribers A-1 through A-n. In this way, the subscribers A-1 through A-n receive "asian\_news.xml" and "world\_news.xml".

Then, the Asian branch system 221 deletes the structure information portion (5) from the structure information portion (4). As a result, structure information portion (6) is left. The Asian branch system 221 delivers the structure information portion (6) to the Japanese branch system (japan@delivery.com.jp) 231 according to the

description of the delivery\_info tag in the structure information portion (6). At this time, the Asian branch system 221 delivers the assembled data "news.xml" to the Japanese branch system 231. The assembled data "news.xml" is generated by the Asian branch system 221, and includes "asian\_news.xml" and "world\_news.xml".

The Japanese branch system 231 analyzes the element data information in the structure information portion (6) shown in Fig. 28 or 32. Namely, the data\_list tag is analyzed. As a result, the assembled data "news.xml" received from the Asian branch system 221, and the element data "japan\_news.xml" stored in a database 232 are recognized. The Japanese branch system 221 extracts the element data "japan\_news.xml" from the database 232.

Next, the Japanese branch system 231 generates complete data from the element data and the received assembled data according to the assembly information in the structure information portion (6). Namely, the delivery data is generated according to the description of the structure tag. The assembly information is exemplified in Fig. 37. In this assembly information, assembled data "news.xml"

received from the Asian branch system 221, and "japan\_news.xml" extracted from the database 232 are specified as data to be delivered. Here, the assembled data "news.xml" received from the Asian  
 5 branch system 221 includes "asian\_news.xml" and "world\_news.xml" as described above.

Fig. 38 is shows an example of the complete data generated according to the assembly information in the structure information portion (6) in the  
 10 Japanese branch system 231. In this complete data, "japan\_news.xml", "asian\_news.xml", and "world\_news.xml" are respectively embedded into the japan\_news tag, the asian\_news tag, and the world\_news tag.

15 The Japanese branch system 231 delivers the complete data to delivery destinations according to the delivery destination information in the structure information portion (6). Namely, the data delivery is executed according to the  
 20 description of the receptionist\_list tag. However, the addresses of the delivery destinations are not described in the receptionist\_list tag, but only a category "japan" is specified in the receptionist-list tag. Accordingly, the Japanese  
 25 branch system 231 accesses a subscriber list 233

by using this category name as a key, recognizes the delivery destinations belonging to the category "japan", and delivers the complete data including "asian\_news.xml", "world\_news.xml", and "japan\_news.xml" to the subscribers J-1 through J-n. In this way, the subscribers J-1 through J-n who make a contract with the Japanese branch receive "asian\_news.xml", "world\_news.xml", and "japan\_news.xml".

10 Then, the Japanese branch system 231 deletes the structure information portion (6) from the received structure information. In this case, no data is left as the structure information. Accordingly, the entire process is regarded as being  
15 completed, and the data delivery process is terminated in the Japanese branch system 231.

In the above described embodiments, one branch office system delivers common data to a plurality of subscribers. With the data delivering system  
20 according to the present invention, however, a branch office system can deliver individual data depending on each subscriber according to a description of structure information.

Fig. 39 exemplifies the assembly information  
25 in the structure information used when data that

differs depending on each subscriber is delivered. Exemplified here is the assembly information for the data to be delivered from the Japanese branch system 231 to a certain subscriber. In this assembly  
5 information, "personal\_news.xml" is specified as data to be delivered to the subscriber in addition to "news.xml" and "japan\_news.xml".

Fig. 40 explains a method collecting element data for each subscriber. Illustrated here is the  
10 operations of the Japanese branch system 231 which generates complete data according to the assembly information shown in Fig. 39.

When recognizing that "personal\_news.xml" is specified in the assembly information, the Japanese  
15 branch system 231 accesses a personal news database 234 by using the subscriber address to which data is to be delivered as a key. The personal news database 234 manages the genres which are preselected by the subscriber for each delivery destination  
20 address. Here, the genres are, for example, politics, sports, the economy, international topics, society news, etc.

Then, the Japanese branch system 231 collects corresponding element data from a genre-by-genre  
25 news database 235 based on the genre information



obtained from the personal news database 234. As a result, "personal\_news.xml" for each subscriber can be obtained. The Japanese branch system 231 then delivers "personal\_news.xml" to the subscriber  
5 along with "world\_news.xml", etc.

The capabilities implementing the above described data deliveries (the delivery source system, the relay system, the resource system, and the delivery destination system) are realized by  
10 executing programs describing the above described processes with a computer. The block diagram of the computer 300 executing the programs is shown in Fig. 41.

A CPU 301 loads the programs describing the  
15 processes shown in the above described flowcharts from a storage device 302 into a memory 303, and executes the programs. The storage device 302 is, for example, a hard disk, and stores the above described programs. The memory 303 is, for example,  
20 a semiconductor memory, and is used as a working area of the CPU 301.

A storage medium driver 304 accesses a portable storage medium 305 according to an instruction of the CPU 301. The portable storage medium 305 is,  
25 for example, a semiconductor device (PC card, etc.),

a medium (a floppy disk, a magnetic tape, etc.)  
to/from which information is input/output by a  
magnetic operation, a medium (optical disk, etc.)  
to/from which information is input/output by an  
5 optical operation, and the like. A communication  
controlling device 306 transmits/receives data  
to/from a network according to an instruction of  
the CPU 301.

Fig. 42 explains the method providing software  
10 programs, etc. relating to the present invention.  
The programs relating to the present invention are  
provided, for example, with any of the following  
methods.

(a) The programs are installed in the computer 300,  
15 and provided. In this case, the programs, etc. are  
pre-installed prior to shipment.

(b) The programs are stored onto a portable storage  
medium and provided. In this case, the programs,  
etc., which are stored onto the portable storage  
20 medium 305, are fundamentally installed in the  
storage device 302 via the storage medium driver  
304.

(c) The programs are provided from a server on a  
network. In this case, the programs, etc., which  
25 are stored in the server, are fundamentally obtained

by being downloaded by the computer 300.

According to the present invention, a delivery source system does not need to collect all of data to be delivered, so that the load on the delivery source system is reduced. Additionally, the delivery source system does not need to recognize individual delivery destinations, thereby facilitating address management, etc. in the delivery source system. Furthermore, element data can be assembled by devices other than a delivery source device, whereby the load on the delivery source system is reduced. Still further, an optimum device for which a load distribution is considered collects data, leading to an increase in a data delivery efficiency.

**What is claimed is:**

1. A data delivering method delivering data to a device which is connected to a network, comprising:

5 transmitting structure information including information for collecting element data from a first device to a second device;

collecting element data by the second device according to the structure information; and

10 transmitting the element data collected by the second device to a third device.

2. A data delivering method delivering data to a device which is connected to a network,

15 comprising:

generating structure information including first information for identifying element data to be delivered to a destination device, second information for identifying a device which collects the element data, and third information for identifying the destination device;

collecting element data according to the first information by the device identified by the second information; and

25 delivering the collected element data from the

device identified by the second information to the destination device identified by the third information.

5           3.     The method according to claim 2, wherein  
              the structure information includes fourth  
information for assembling collected element data;  
and

              the collected element data is delivered to the  
10 destination device after being assembled by the  
device identified by the second information  
according to the fourth information.

              4.     The method according to claim 2, wherein:  
15           the structure information includes fourth  
information for assembling collected element data;  
and

              the collected element data is assembled by the  
destination device according to the fourth  
20 information.

              5.     The method according to claim 2, wherein:  
              the third information specifies a destination  
group including a plurality of destination devices;  
25 and

the device identified by the second information delivers the element data to the plurality of destination devices belonging to the destination group specified by the third  
5 information.

6. The method according to claim 2, wherein the destination device identified by the third information is set as the device identified by the  
10 second information in the structure information.

7. A data delivering method delivering data from a source device to a destination device in a system including the source device, a first relay  
15 device, a second relay device connected to the first relay device in series, and the destination device, comprising:

generating structure information by the source device;  
20 collecting first element data by the first relay device according to the structure information;  
collecting second element data by the second relay device according to the structure information;  
and  
25 delivering the first and the second element



delivering the first and the third element data from the third relay device to a destination device connected to the third relay device.

- 5           10. A data delivering method delivering data from a source device to a destination device in a system including the source device, a first relay device, a plurality of second relay devices arranged in parallel, comprising:
  - 10           generating, by the source device, structure information including information specifying a relay device group including a plurality of second relay devices;
    - collecting first element data by the first
    - 15 relay device according to the structure information;
      - recognizing, by the first relay device, the plurality of second relay devices belonging to the relay device group specified by the structure information;
    - 20           delivering the first element data to the plurality of second relay devices;
      - respectively collecting element data by the plurality of second relay devices according to the structure information; and
      - 25           delivering the first element data and the



[illegible][illegible][illegible][illegible][illegible]

**06** **07** **08** **09** **10** **11** **12**

a second device which receives the structure information from said first device, collects the element data according to the first information, and delivers the collected element data to the destination device according to the third information, when identified by the second information.

- 10           13. A data delivering system delivering data from a source device to a destination device in a system including the source device, a first relay device, a second relay device connected to the first relay device in series, and the destination device,
- 15           said source device generates structure information,
- said first relay device collects first element data and transmits it to said second relay device according to the structure information,
- 20           said second relay device collects second element data and delivers the first and second element data according to the structure information.

14. A data delivering system delivering data
- 25           from a source device to a destination device in a

system including the source device, a first relay device, and second and third relay devices arranged in parallel,

5       said source device generates structure information,

      said first relay device collects first element data and transmits it to the second and third relay devices according to the structure information,

10       said second relay device collects second element data and delivers the first and second element data to a destination device connected to said second relay device according to the structure information,

15       said third relay device collects third element data and delivers the first and third element data to a destination device connected to said third relay device according to the structure information.

20       15. A delivery source device, arranged in a data delivering system where structure information including first information for identifying element data to be delivered to a destination device, second information for identifying a device that collects the element data, and third information for  
25       identifying the destination device is generated,

the device identified by the second information collects the element data according to the first information, and the collected element data is delivered from the device identified by the second information to the destination device identified by the third information, comprising:

a generating unit generating the structure information; and

a transferring unit transferring the structure information to the device identified by the second information.

16. A relay device, arranged in a data delivering system where structure information including first information for identifying element data to be delivered to a destination device, second information for identifying the relay device that collects the element data, and third information for identifying the destination device is generated by a delivery source device, and the element data identified by the first information is collected and delivered to the destination device according to the third information, comprising:

a collecting unit collecting element data according to the first information; and

a transferring unit transferring the element data collected by said collecting unit to the destination device identified by the third information.

5

17. A storage medium having computer readable program code, comprising:

first program code generating structure information including first information for  
10 identifying element data to be delivered to a destination device, second information for identifying a device that collects the element data, and third information for identifying the destination device; and

15 second program code transferring the structure information to a device identified by the second information.

18. A storage medium having computer  
20 readable program code, comprising:

first program code analyzing structure information including first information for  
identifying element data to be delivered to a destination device, and second information for  
25 identifying the destination device;

second program code collecting element data according to the first information; and

third program code transferring the element data to the destination device according to the

5 second information.

**Abstract of the Disclosure**

A headquarters system generates structure information, and obtains nationwide news from a resource system according to the structure information. The headquarters system delivers the structure information and the nationwide news to a branch system. The branch system obtains local news from a resource system according to the structure information received from the headquarters system, and delivers the nationwide news and the local news to a plurality of destinations according to the structure information.

The diagram illustrates the system architecture. A central processing unit is divided into four vertically stacked functional blocks: a DATA STORING UNIT at the top, followed by a DATA MANAGING UNIT, a DATA TRANSFERRING UNIT, and a COMMUNICATION CONTROLLING UNIT at the bottom. These units are interconnected by vertical lines. The COMMUNICATION CONTROLLING UNIT is connected to a USER, indicated by an upward arrow and a downward arrow. The DATA STORING UNIT is connected to a DELIVERY DATA database (represented by a cylinder) via a line labeled 502. The DATA MANAGING UNIT is labeled 501, the DATA TRANSFERRING UNIT is labeled 503, and the COMMUNICATION CONTROLLING UNIT is labeled 504.

FIG. 1







FIG. 2



F I G. 3 A

ELEMENT DATA- 1	DESTINATION INFORMATION- 1
ELEMENT DATA- 2	DESTINATION INFORMATION- 2
ELEMENT DATA- 3	DESTINATION INFORMATION- 3
...	...
ELEMENT DATA- n	DESTINATION INFORMATION- n

F I G. 3 B




FIG. 4




FIG. 5




FIG. 6





FIG. 7





F I G. 9



RELAY SYSTEM INFORMATION	ASSEMBLY INFORMATION	ELEMENT DATA INFORMATION 1	...	ELEMENT DATA INFORMATION n	DELIVERY DESTINATION INFORMATION
-----------------------------	-------------------------	-------------------------------	-----	-------------------------------	--

FIG. 10A




FIG. 10B

RELAY SYSTEM INFORMATION	ASSEMBLY INFORMATION	ELEMENT DATA INFORMATION 1	...	ELEMENT DATA INFORMATION n	DELIVERY DESTINATION INFORMATION 1	...	DELIVERY DESTINATION INFORMATION m
--------------------------------	-------------------------	-------------------------------------	-----	-------------------------------------	---	-----	---

FIG. 11A

DELIVERY SOURCE SYSTEM 6 1      RELAY SYSTEM 7 1      DELIVERY DESTINATION SYSTEM 8 1  
1    ...    m






FIG. 11B







FIG. 13

001260-5222-9920



F I G . 1 4





FIG. 17






FIG. 18




FIG. 19




FIG. 20




FIG. 21

HEADQUARTERS SYSTEM	ATTACH	NATIONWIDE NEWS			
BRANCH A SYSTEM	ASSEMBLED DATA + LOCAL NEWS	LOCAL NEWS	DELIVERY DESTINATION A-1	...	DELIVERY DESTINATION A-n
BRANCH B SYSTEM	ASSEMBLED DATA + LOCAL NEWS	LOCAL NEWS	DELIVERY DESTINATION B-1	...	DELIVERY DESTINATION B-n
BRANCH C SYSTEM	ASSEMBLED DATA + LOCAL NEWS	LOCAL NEWS	DELIVERY DESTINATION C-1	...	DELIVERY DESTINATION C-n

FIG. 22

HEADQUARTERS SYSTEM	ATTACH	NATIONWIDE NEWS	
BRANCH A SYSTEM	ASSEMBLED DATA+LOCAL NEWS	LOCAL NEWS	SUBSCRIBER
BRANCH B SYSTEM	ASSEMBLED DATA+LOCAL NEWS	LOCAL NEWS	SUBSCRIBER
BRANCH C SYSTEM	ASSEMBLED DATA+LOCAL NEWS	LOCAL NEWS	SUBSCRIBER

FIG. 23

GROUP NAME	DELIVERY DESTINATION
SUBSCRIBERS	A - 1 A - 2 ⋮ A - n
BUSINESS PARTNERS	X - 1 X - 2 ⋮ X - m
}	}

F I G. 24




FIG. 25








FIG. 27




FIG. 28

```

<!--NewYork-->
<delivery_info>
  <gateway>newyork@delivery.com</gateway>
  <structure>http://www.delivery.com/structure/news.xml</structure>
  <data_list>
    <news>http://www.delivery.com/world_news.xml</news>
  </data_list>
  <receptionist_list>
    <receptionist>U-l@foo.com</receptionist>
    ...
    <receptionist>U-n@foo.com</receptionist>
  </receptionist_list>

```

F I G. 29

```
<!--Yugoslavian-->
<delivery_info>
  <gateway>yugo@delivery.com</gateway>
  <data_list>
    <news>news.xml</news>
  </data_list>
  <receptionist_list>
    <receptionist>Y-1@foo.com</receptionist>
    ...
    <receptionist>Y-n@foo.com</receptionist>
  </receptionist_list>
```

F I G. 30

<!--Asia-->  
<delivery\_info>  
 <gateway>asia@delivery.com</gateway>  
 <structure>http://asia.delivery.com/structure/news.xml</structure>  
 <data\_list>  
 <news>news.xml</news>  
 <news>http://asia.delivery.com/asian\_news.xml</news>  
 </data\_list>  
 <receptionist\_list>  
 <category>asia</category>  
 </receptionist\_list>

F I G. 3 1

```

<!--Japan-->
<delivery_info>
  <gateway>japan@delivery.co.jp</gateway>
  <structure>http://www.delivery.co.jp/structure/japan.xml</structure>
  <data_list>
    <news>news.xml</news>
    <news>http://www.delivery.co.jp/japan_news.xml</news>
  </data_list>
  <receptionist_list>
    <category>japan</category>
  </receptionist_list>

```

F I G. 3 2







```
<?xml version="1.0"?>
<!DOCTYPE daily_news [
<!ENTITY news SYSTEM "news.xml">
<!ENTITY asian_news SYSTEM "asian_news.xml">
]>

<dialy_news>
<date>2yyy-yy-yy</date>
<edition>yy</edition>
&asian_news;
&news;
</daily_news>
```

F I G. 35

```
<daily_news>
<date>2yyy-yy-yy</date>
<edition>yy</edition>
<asian_news>
. . . . .
. . . . .
. . . . .
</asian_news>
<daily_news>
<date>2xxx-xx-xx</date>
<edition>xx</edition>
<world_news>
. . . . .
. . . . .
</world_news>
</daily_news>
</daily_news>
```

FIG. 36

```
<?xml version="1.0"?>
<!DOCTYPE daily_news> [
<!ENTITY news SYSTEM "news.xml">
<!ENTITY japan_news SYSTEM "japan_news.xml">
]>

<dialy_news>
<date>2zzz-zz-zz</date>
<edition>zz</edition>
&japan_news;
&news;
</daily_news>
```

F I G. 37




```
<?xml version="1.0"?>

<!DOCTYPE daily_news> [
<!ENTITY news SYSTEM "news.xml">
<!ENTITY japan_news SYSTEM "japan_news.xml">
<!ENTITY personal_news SYSTEM "personal_news.xml">
]>

<dialy_news>
<date>2zzz-zz-zz</date>
<edition>zz</edition>
&personal_news;
&japan_news;
&news;
</daily_news>
```

FIG. 39

DELIVERY ADDRESS	GENRE 1	GENRE 2	. . .	GENRE n
J-1@foo.ne.jp	on	off		on
⋮				
J-n@foo.ne.jp	off	on		off



F I G. 4 0




FIG. 41






FIG. 42

## Declaration and Power of Attorney For Patent Application

### 特許出願宣言書及び委任状

### Japanese Language Declaration

### 日本語宣言書

下記の氏名を発明者として、私は以下の通り宣言します。

As a below named inventor, I hereby declare that:

私の住所、私寓番、国籍は下記の私の氏名の後に記載された通りです。

My residence, post office address and citizenship are as stated next to my name.

下記の名称の発明に関して請求範囲に記載され、特許出願している発明内容について、私が最初かつ唯一の発明者（下記の氏名が一つの場合）もしくは最初かつ共同発明者であると（下記の名称が複数の場合）信じています。

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

### DATA DELIVERING SYSTEM

上記発明の明細書（下記の欄でX印がついていない場合は、本書に添付）は、

the specification of which is attached hereto unless the following box is checked:

☐ 月 日に提出され、米国出願番号または特許協定条約国際出願番号を \_\_\_\_\_ とし、  
（該当する場合） \_\_\_\_\_ に訂正されました。

☐ was filed on \_\_\_\_\_  
as United States Application Number or  
PCT International Application Number  
\_\_\_\_\_ and was amended on  
\_\_\_\_\_ (if applicable).

私は、特許請求範囲を含む上記訂正後の明細書を検討し、内容を理解していることをここに表明します。

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

私は、連邦規則典第37編第1章56項に定義されるとおり、特許資格の有無について重要な情報を開示する義務があることを認めます。

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56.

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

Japanese Language Declaration  
(日本語宣言書)

私は、米国法典第35編119条(a)-(d)項又は365条(b)項に基づき下記の、米国以外の国の少なくとも一ヶ国を指定している特許協力条約365(a)項に基づき国際出願、又は外国での特許出願もしくは発明者証の出願についての外国優先権をここに主張するとともに、優先権を主張している。本出願の前に出願された特許または発明者証の外国出願を以下に、枠内をマークすることで、示しています。

## Prior Foreign Application(s)

外国での先行出願

11-341709

(Number)

(番号)

Japan

(Country)

(国名)

1st/December/1999

(Day/Month/Year Filed)

(出願年月日)

Priority Not Claimed

優先権主張なし

☐

(Number)

(番号)

(Country)

(国名)

(Day/Month/Year Filed)

(出願年月日)

☐

私は、第35編米国法典119条(e)項に基づいて下記の米国特許出願規定に記載された権利をここに主張いたします。

(Application No.)

(出願番号)

(Filing Date)

(出願日)

(Application No.)

(出願番号)

(Filing Date)

(出願日)

私は、下記の米国法典第35編120条に基づいて下記の米国特許出願に記載された権利、又は米国を指定している特許協力条約365条(c)項に基づき権利をここに主張します。また、本出願の各請求範囲の内容が米国法典第35編112条第1項又は特許協力条約で規定された方法で先行する米国特許出願に開示されていない限り、その先行米国出願書提出日以降で本出願書の日本国内または特許協力条約国際提出日までの期間中に入手された、連邦規則法典第37編1条56項で定義された特許資格の有無に関する重要な情報について開示義務があることを認識しています。

(Application No.)

(出願番号)

(Filing Date)

(出願日)

(Status: Patented, Pending, Abandoned)

(現況: 特許許可済、係属中、放棄済)

(Application No.)

(出願番号)

(Filing Date)

(出願日)

(Status: Patented, Pending, Abandoned)

(現況: 特許許可済、係属中、放棄済)

私は、私自身の知識に基づいて本宣言書中で私が行う宣言が真実であり、かつ私の入手した情報と私の信じていることに基づき宣言が全て真実であると信じていること、さらに故意にされた虚偽の表明及びそれと同等の行為は米国法典第18編1001条に基づき、罰金または拘禁、もしくはその両方により処罰されること、そしてそのような故意による虚偽の表明を行えば、出願した、又は差に許可された特許の有効性が失われることを認識し、よってここに上記のごとき宣誓を致します。

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

## Japanese Language Declaration

(日本語宣言書)

各作状： 私は下記の発明者として、本出願に関する一切の手続きを米特許庁に対して遂行する弁理士または代理人として、下記の者を指名いたします。(弁理士、または代理人氏名及び登録番号を明記のこと)

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith (list name and registration number)

James D. Halsey, Jr., 22,729; Harry John Staas, 22,010; David M. Pitcher, 25,908; John C. Garvey, 28,607; J. Randall Beckers, 30,358; William F. Herbert, 31,024; Richard A. Gollhofer, 31,106; Mark J. Henry, 36,162; Gene M. Garner II, 34,172; Michael D. Stein, 37,240; Paul I. Kravetz, 35,230; Gerald P. Joyce, III, 37,648; Todd E. Mariette, 35,269; Harlan B. Williams, Jr., 34,756; George N. Stevens, 36,938; Michael C. Soldner, P-41,453 and William M. Schertler, 35,348 (agent)

書類送付先

Send Correspondence to:

STAAS & HALSEY  
700 Eleventh Street, N.W.  
Suite 500  
Washington, D.C. 20001

直接電話連絡先：(名前及び電話番号)

Direct Telephone Calls to: (name and telephone number)

STAAS & HALSEY  
(202) 434-1500

唯一または第一発明者名		Full name of sole or first inventor	
Yasutaka ODA		Yasutaka ODA	
発明者の署名	日付	Inventor's signature	Date
<i>Yasutaka Oda</i>		<i>Yasutaka Oda</i>	Sep. 1, 2000
住所		Residence	
		Kobe, Japan	
国籍		Citizenship	
		Japan	
私書箱		Post Office Address	
		c/o FUJITSU KOBE ENGINEERING LIMITED, 1-15, Kano-cho 2-chome, Chuo-ku, Kobe-shi, Hyogo 650-0001, Japan	
第二共同発明者		Full name of second joint inventor, if any	
Katzumi HAYASHI		Katzumi HAYASHI	
第二共同発明者	日付	Second inventor's signature	Date
<i>Katzumi Hayashi</i>		<i>Katzumi Hayashi</i>	Sep. 1, 2000
住所		Residence	
		Kobe, Japan	
国籍		Citizenship	
		Japan	
私書箱		Post Office Address	
		c/o FUJITSU KOBE ENGINEERING LIMITED, 1-15, Kano-cho 2-chome, Chuo-ku, Kobe-shi, Hyogo 650-0001, Japan	

(第三以降の共同発明者についても同様に記載し、署名をすること)

(Supply similar information and signature for third and subsequent joint inventors.)

第三共同発明者	Full name of third joint inventor, if any Masaya KIMURA	
第三共同発明者	日付	Third inventor's signature Masaya Kimura Date Sep. 1, 2000
住 所	Residence Kobe, Japan	
国 籍	Citizenship Japan	
私書箱	Post Office Address c/o FUJITSU KOBE ENGINEERING LIMITED, 1-15, Kano-cho 2-chome, Chuo-ku, Kobe-shi, Hyogo 650-0001, Japan	
第四共同発明者	Full name of fourth joint inventor, if any Taichi UJIGAWA	
第四共同発明者	日付	Fourth inventor's signature Taichi Ujigawa Date Sep. 1, 2000
住 所	Residence Kobe, Japan	
国 籍	Citizenship Japan	
私書箱	Post Office Address c/o FUJITSU KOBE ENGINEERING LIMITED, 1-15, Kano-cho 2-chome, Chuo-ku, Kobe-shi, Hyogo 650-0001, Japan	

第五共同発明者	Full name of fifth joint inventor, if any	
第五共同発明者	日付	Fifth inventor's signature Date
住 所	Residence	
国 籍	Citizenship	
私書箱	Post Office Address	
第六共同発明者	Full name of sixth joint inventor, if any	
第六共同発明者	日付	Sixth inventor's signature Date
住 所	Residence	
国 籍	Citizenship	
私書箱	Post Office Address	

(第七以降の共同発明者についても同様に  
記載し、署名をすること)

(Supply similar information and signature for  
seventh and subsequent joint inventors.)